muRata Inductor Data S	Sheet				
LQW15AN5N5B80# "#" indicates a package specification code.					
In Production General 125 Wound (Non) LowRdc (Mind) Tight (White OK) Reaction OK Reaction					
< List of part numbers with package codes > LQW15AN5N5B80D , LQW15AN5N5B80B					
Shape		Note	25		
	n)	necessar Please ap operating Please co	ng temperature exceeding +85°C, α γ for LQW15A_80 series. oply the derating curve shown in ch temperature. onfirm "Notice (Rating)". Prences Specifications Φ180mm Paper taping		
L size	1.0 ±0.1mm	В	Packing in bulk	500	
W size	0.6 ±0.1mm				
T size	0.5 ±0.1 mm		Mass (Typ.)		
Size code in inch (mm)	0402 (1005)	1 piece 0.0009g			

Specifications

Inductance	5.5nH ±0.1nH
Inductance test frequency	100MHz
Rated current (Itemp) (Based on Temperature rise)	1770mA
Max. of DC resistance	0.040Ω
Q (min.)	35
Q test frequency	250MHz
Self resonance frequency (min.)	8.0GHz
Operating temperature range (Self-temperature rise is not included)	-55∼125°C
Series	LQW15AN_80

🔔 Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Q-Frequency characteristics (Typ.)







2 of 2

🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.