

## Miscellaneous Suppression Cores (2643165151)



Part Number: 2643165151

43 SPLIT ROUND CABLE CORE

## **Explanation of Part Numbers:**

- Digits 1 & 2 = Product Class
- − Digits 3 & 4 = Material Grade

Fair- Rite has tooled several special core geometries in the 43 & 77 material for suppression of conducted EMI.

 $\Box$ For any non- catalog suppression core design feel free to contact our customer service or application group for feasibility and availability.

The "C" dimension, the core length, can be modified to suit specific applications.

## Weight: 109 (g)

mm	mm tol	nominal inch	inch misc.	
82.6	±1.60	3.25		
13.1	±0.30	0.516	_	
28	±0.70	1.1	_	
12.95	±0.25	0.51	_	Chart Legend + Test frequency
19.05	±0.40	0.75	_	Figures 3 & 4 tested in pairs
	13.1 28 12.95	82.6 ±1.60 13.1 ±0.30 28 ±0.70 12.95 ±0.25	82.6 ±1.60 3.25 13.1 ±0.30 0.516 28 ±0.70 1.1 12.95 ±0.25 0.51	82.6 ±1.60 3.25

Typical Impedance	
10 MHz	100
25 MHz <sup>+</sup>	163
100 MHz <sup>+</sup>	280
250 MHz	340

These suppression cores are controlled for impedance only. The minimum impedance is typically the listed impedance less 20%. Single turns tests are performed on the 4193A Vector Impedance Analyzer with the shortest practical wire length.