KEMET Part Number: T491X476K035ZT7280 Obsolete



B45196H, Tantalum, MnO2 Tantalum, 47 uF, 10%, 35 V, SMD, Molded, 7343, Height Max = 4.4mm



General Information	
Supplier:	KEMET
Series:	B45196H
Dielectric:	MnO2 Tantalum
Style:	SMD Chip
Description:	SMD, Molded
RoHS:	Yes
Termination:	Tin
Notes:	Obsolete. Old Part Number [Obsolete] Was B45196H6476K506

Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	4.1mm +/-0.3mm
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
К	1.8mm TYP

Packaging Specifications		
Packaging:	T&R, 330mm	
Packaging Quantity:	1800	

Specifications		
Capacitance:	47 uF	
Capacitance Tolerance:	10%	
Voltage DC:	35 VDC (85C), 23.45 VDC (125C)	
Temperature Range:	-55/+125C	
Rated Temperature:	85C	
Dissipation Factor:	6%	
Failure Rate:	N/A	
Leakage Current:	16 uA	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

