
KEMET Part Number: M3253508E1Z184JZMB

(C2220K184J3EML)



SMD MIL COG PRF32535, Ceramic, Military/High Reliability, 0.18 uF, 5%, 25 VDC, COG, SMD, Low ESR, MIL-PRF-32535, N/A, 2220



RoHS: No Termination: Solder Plated Failure Rate: N/A	Supplier:	KEMET
Description: SMD, Low ESR, MIL-PRF-325 RoHS: No Termination: Solder Plated Failure Rate: N/A	Series:	SMD MIL COG PRF32535
RoHS: No Termination: Solder Plated Failure Rate: N/A	Style:	SMD Chip
Termination: Solder Plated Failure Rate: N/A	Description:	SMD, Low ESR, MIL-PRF-32535
Failure Rate: N/A	RoHS:	No
1 411411 4 11411	Termination:	Solder Plated
Qualifications: MIL-DDE-32535 M-L aval	Failure Rate:	N/A
Qualifications. WIL-FIXE-32333 W-Level	Qualifications:	MIL-PRF-32535 M-Level
Chip Size: 2220	Chip Size:	2220

General Information

Dir	nensions
	5.69mm +/-0.41mm
_	(0.224 in +/-0.016 in)
W	5mm +/-0.41mm (0.197 in +/-0.016 in)
T	2.79mm MAX (0.11 in MAX)
В	0.64mm +/-0.46mm
	(0.025 in +/-0.018 in)

Specifications	
Capacitance:	0.18 uF
Capacitance Tolerance:	5%
Voltage DC:	25 VDC
Dielectric Withstanding Voltage:	62.5 V
Temperature Range:	-55/+125C
Temperature Coefficient:	COG
Dissipation Factor:	0.25% 1MHz 25C
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	5.56 GOhms

Packaging S	pecifications
Packaging:	Waffle
Packaging Quantity:	20

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

